

Panthera U3 Light - Order form



Dealer Name*:

Account #*:

City, Post Code, Country:

Phone:

Email:

P.O. Number

Clinician:

Client Reference*:

Client Weight:

Rep Name:

*Required field

Special considerations that need to be addressed here (e.g., diagnosis):

Chassis

Standard configurations include tapered frame with front frame angle 100°, seat angle 7°, calf strap, standard colour option, backrest, fixed rear wheel position with 2° camber, front castors, rigid footplate, push to lock brakes and Spinergy X rear wheels with aluminium handrims. Seat height with 24" wheels: front 47 cm, rear 43 cm. Seat height can be adjusted with different size rear wheels. 100kg weight limit.

G557	U3 Light	Seat width 33-45cm, seat depth 35-46cm.	\$
G557	U3 Light/L	More easily balanced, rear axle is positioned 22mm forward. Seat width 33-45cm, seat depth 35-46cm.	\$
G5801	U3 Light Y Front	Chassis gives full frame width for user's thighs. Seat width 33-45cm, seat depth 35, 37.5, 40, 42.5cm. <i>Extended model not kept in stock, longer leadtime.</i>	\$
G5801	U3 Light Y Front/L	Chassis gives full frame width for user's thighs and more easily balanced, rear axle is positioned 22mm forward. Seat width 33-45cm, seat depth 35, 37.5, 40, 42.5cm. <i>Extended model not kept in stock, longer leadtime.</i>	\$
G5806	U3 Light Y Front 90°	Chassis gives full frame width for user's thighs and 90° front frame angle. Seat width 33-45cm, seat depth 35, 37.5. <i>Extended model not kept in stock, longer leadtime.</i>	\$
G5809	U3 Light Y Front Low	Chassis gives full frame width for user's thighs and 2.5cm lower than U3 Light. Seat width 33-45cm, seat depth 35, 37.5, 40, 42.5cm. <i>Extended model not kept in stock, longer leadtime.</i>	\$
G5808	U3 Light Y Front High 4°	Chassis gives full frame width for user's thighs, higher seat height and 4° seat angle. Seat width 33-50cm, seat depth 35, 37.5, 40, 42.5cm. <i>Extended model not kept in stock, longer leadtime.</i>	\$

Chassis Colour

Standard Colours:	White Pearl*	Anodic Black				
Optional Colours:	Blue Classic	Mean Green	Panorange	Brave Bronze	Grey Metallic	Telemagenta
	Racing Blue	Ruby Red	Sting Yellow	Horizon Grey	Pine Green	Pearl Violet
	White Pearl*					

White Pearl standard option for U3 Light and U3 Light/L, non-standard for other variants. *Non-standard colours require additional delivery time of 20 days. Additional information [here](#).*

Seat Measurements

Seat Width: 33cm 36cm 39cm 42cm 45cm

Check allowed seat width based on chassis selection.

Seat Depth: 35cm 37.5cm 40cm 42.5cm

Check allowed seat depth based on chassis selection.

Backrest

Standard Backrest	25-35cm range.	Standard
Tapered Backrest 3cm	30-35cm range.	\$
Tapered Backrest 6cm	30-35cm range. <i>Additional delivery time of 20 days.</i>	\$
Flared Backrest 3cm	25-35cm range. <i>Additional delivery time of 20 days.</i>	\$
Curved Backrest	25-35cm range.	\$
Curved Tapered Backrest	35cm. <i>Additional delivery time of 20 days.</i>	\$
Frame for Solid Backrests	35cm. <i>Backrest frame still folds.</i>	\$
Backrest Height:	25cm 30cm 35cm	
	<i>Check allowed height based on backrest selection.</i>	

Chassis Balance

COG Position:	A Least easy balanced	B Medium balance	C Most easy balanced
	<i>Can be easily changed after manufacture.</i>		

Rear Wheels

Rear Wheels

Spinergy X Wheels:	24" 25" 26"	Standard
	Black Spokes White Spokes	

Tyres

Schwalbe Right Run 22"(501), 24"(540), 25" (559), 26"(590)	Standard
Rugged 24" (540)	\$
Schwalbe Marathon Plus 24"(540), 25" (559), 26"(590)	\$
Schwalbe One 24"(540), 25" (559)	\$
PU 24" <i>Not compatible with reTyre skins.</i>	\$

Handrims

190DD30-C	Aluminium	Standard
190DD11-C	Titanium	\$
19051DDBT-C	Paragrip	\$
19052DDBT-C	Tetragrip	\$
19030DD-C	Maxgrip 22" and 24" only.	\$
19044DD	Aluminium X	\$

Front Wheels

Castor Selection:	90mm (3.5") X	90mm (3.5")	120mm (4.7")
--------------------------	---------------	-------------	--------------

Footrest

36915BB-C	U-Shape Footplate	Standard
36006BB-C	U-Shape Footplate, Extended	No charge
36916BB-C	U-Shape Footplate, Small Heel Bar	No charge
65050BB-C	Carbon Footplate	\$
65150BB-C	Angle-Adjustable Footplate	\$
36004BB-C	U-Shape Footplate, X	\$
65060BB-C	Carbon Footplate, X	\$
36010BB-C	Plastic Plate for Rigid Footrest	\$

Wheel Locks

4630000-C	Push to Lock	Standard
4630150-C	Wheel Lock Blades <i>For solid PU tyres. Not with one hand brakes.</i>	\$
367BBBB-C	One Hand Brake, Right Activation	\$
368BBBB-C	One Hand Brake, Left Activation	\$

Side Guards / Armrests

No Side Guards	Standard
Standard Side Guards	\$
Carbon Side Guards, Without Fender	\$
Carbon Side Guards, Small Fender	\$
Carbon Side Guards, Large Fender	\$
Side Guards With Arm Supports	\$

Push Handles

No Push Handles	Standard
4245000-C Foldable Push Handles	\$

Accessories

Cushions

572BB40-C	Seat Cushion, 2.5cm	\$
575BB40-C	Seat Cushion, 5cm	\$
57710BB-C	Wedge Cushion <i>Used to alter seat angle.</i>	\$
990021X-C	Seat Bag	\$
	Mounted On Seat Upholstery Mounted Under Cushion	

Other Accessories

9900251-C	Tube Protection, Front	\$
9900251-C	Tube Protection, Rear	\$
6810020-C	Tray Table <i>Only together with arm supports.</i>	\$
9900301-C	Crutch Holder	\$
9900261-C	Backpack	\$
reTyre Skins		\$
24" 25" 26"		
260010X-C	FreeWheel Attachment <i>Required angle-adjustable footplate.</i>	\$

Set-Up Adjustments

Backrest Angle: Specify (mm) | A =
10-20mm, 18mm standard.


Footrest Heights: Specify (mm) | A = Specify (mm) | B = Specify (mm) | K =
'B' only required for angle adjustable footrests.

Notes

Reference Diagrams



Backrest Angle



Footrest Height