



PDG Stellar GLT - Order Form



Dealer Name*:

Account #*:

City, Post Code, Country:

Phone:

Email:

P.O. Number

Clinician:

Client Reference*:

Client Weight:

Rep Name:

*Required field

Special considerations that need to be addressed here (e.g., diagnosis):

Wheelchair & Frame

Stellar GLT 45° Manual Tilt Wheelchair *Lightweight aluminum frame. Aluminum frame is not recommended for agitated users.*

\$

Frame Type | All frames offer 300lbs (136kg) weight capacity.

Fixed Frame Width *Select a fixed seat width below.*

No charge

Adjustable Width Frame *Select an adjustable seat width below.*

\$

User Weight | Required for setup of tilt uplift force.

User Weight Range:	Up to 75lbs (34kg)	75lbs - 100lbs (34kg - 45kg)	100lbs - 115lbs (45kg - 52kg)
	115lbs - 150lbs (52kg - 68kg)	150lbs - 200lbs (68kg - 90kg)	200lbs - 250lbs (90kg - 113kg)
	250lbs - 300lbs (113kg - 136kg)		

Frame Options

Transit Tie Down System (TTDS) *Includes 4 factory installed transport brackets. TTDS has been tested according to ANSI/RESNA WC19. See Owners Manual for complete details. Not compatible with seat widths > 22". Tested to maximum weight capacity of 300lbs (136kg).*

No charge

Seat Measurements

Seat Width | Overall chair width is +9.5" with 12"/16" rear wheels, +10.5" with 20"/22"/24" rear wheels.

Fixed:	15"	16"	17"	18"	19"	No charge
	20"	21"	22"	23"		\$
	24"					\$
Adjustable 12"-16":	12"	13"	14"	15"	16"	No charge
Adjustable 15"-20":	15"	16"	17"	18"	19"	No charge
	20"					\$

Seat Depth

Select Depth:	16"	17"	18"	19"	No charge
	20"	21"			\$
	22"				\$

16"-20" seat depths are adjustable.

Frame Finishes

Select Color:	High Gloss Black	Red Pepper	Neon Pink	Ocean Blue Metallic	Tangerine Metallic
	Acid Green Metallic	Midnight Blue Pearl	White Pearl	Black Lava	Titanium Grey
	Pomegranate Red	Blue Mist	Indigo Purple	Hyper Blue	Flame Orange
	OD Green	Silver Streak	Lavendar Dusk	Black Galaxy	Seafoam Green
	Daffodil Yellow				

Armrests

Armrest Type

No Armrests	No charge
Single Post, Height Adjustable Armrests	\$
8"-11" Range 10-14" Range 12"-16" Range	
Fixed Height Armrests, Single Post 12" height, full length arm pads only.	No charge
Armrest Position: Rear Front	

If left blank default setting will be used. In the interest of maintaining chair stability and avoiding interference with other chair functions PDG may not be able to accommodate stated preference.

Armpads

Regular Armpads	No charge
Desk Length 2" x 10" Full Length 2" x 14"	
Waterfall Armpads	\$
Desk Length 2" x 10" Full Length 2" x 14"	
Gel Armpads May interfere with wheels in some tilt configurations.	\$
Narrow 2" x 12" Wide 3.5" x 12"	

Armrest Wideners | Moves armrests outwards by up to 1" each side. Seat size does not change.

Armrest Wideners, 1" Total Additional Width	\$
Armrest Wideners, 2" Total Additional Width	\$

Clothing Guards

Clothing Guards, Single Post Armrests Not compatible with 8"-11" height range.	\$
---	----

Armrest Extensions | Not compatible with flip-up armrests or desk length armpads.

Armrest Extensions - 3" Forward	\$
Armrest Extensions - 3" Rearward	\$

Seat Height

Seat Height - 6" Casters | Seat height is adjustable within the range of the chosen lower frame type (Low/High)

Low						High					
13"	14"	15"	16"	17"	18"	15"	16"	17"	18"	19"	20"
Seat to Floor Height											

Seat Height - 8" Casters | Seat height is adjustable within the range of the chosen lower frame type (Low/High)

Low				High			
15"	16"	17"	18"	17"	18"	19"	20"
Seat to Floor Height							

Seat Pan

No Seat Pan	No charge
Solid Aluminium Seat Pan	\$

Front Casters

Urethane Casters

6" x 1.25" Caster	No charge
8" x 1.25" Caster <i>Only compatible with 16" and 24" rear wheels.</i>	No charge
6" x 1.50" Caster	\$
8" x 2.00" Caster <i>Only compatible with 16" and 24" rear wheels.</i>	\$

Pneumatic Casters

6" x 1.25" Pneumatic Caster	\$
8" x 1.25" Pneumatic Caster <i>Only compatible with 16" and 24" rear wheels.</i>	\$
8" x 2.00" Pneumatic Caster <i>Only compatible with 16" and 24" rear wheels.</i>	\$

Soft-Roll Casters

6" x 1.5" Soft-Roll Caster <i>Urethane tire and silver anodized aluminum hub.</i>	\$
---	----

Frog Legs Suspension Forks

FrogLegs Suspension Forks <i>Only compatible with 16" and 24" rear wheels. Requires 6" soft-roll caster.</i>	\$
--	----

Rear Wheels

Composite Rear Wheel	No charge
12" 16" 20" 22" 24"	

Spoke Rear Wheel	\$
20" 22" 24"	

Rear Wheel Position:	Rear	Front (Default)	No charge
<i>If left blank, default setting will be used. In the interest of maintaining chair stability and avoiding interference with other chair functions, PDG may not be able to accommodate stated preference.</i>			

Axles

Quick Release Rear Axles	No charge
Fixed Rear Axles	No charge

Rear Tires

Urethane Tires	No charge
Pneumatic Tires <i>May result in a finished seat height 1/2" greater than stated.</i>	\$
Pneumatic Tires with Flat-Free Inserts <i>May result in a finished seat height 1/2" greater than stated. Not available with spoke wheels.</i>	\$

Handrimms | Handrimms are only available with 20", 22" and 24" rear wheels.

No Handrimms	No charge
Standard Aluminium Handrimms	No charge
Plastic Coated Handrimms <i>Not compatible with drum brakes.</i>	\$
Projection Handrimms <i>Composite wheels only. 10 projections, 30°, 1-1.8" length.</i>	\$

Wheel Locks

User Wheel Locks	No charge
Push to Lock Pull to Lock	
Attendant Wheel Locks <i>Not compatible with wheel lock extensions.</i>	\$
Push to Lock Pull to Lock	
User and Attendant Wheel Locks <i>Not compatible with drum brakes on 20" rear wheels.</i>	\$
Push to Lock Pull to Lock	
Drum Brakes <i>Available with 12" composite or 20" spoke rear wheels only. Urethane tires only. Not compatible with plastic coated handrimms or two trigger tilt setup.</i>	\$
User Activated Unilateral Wheel Lock <i>Pull to lock. Available up to 20" seat widths only. Not compatible with hill holders.</i>	\$
Left Activation Right Activation	

Wheel Lock Options

Wheel Lock Extensions	<i>Not compatible with attendant wheel lock.</i>	\$
Hill Holders	<i>Requires pneumatic rear tires with flat-free inserts.</i>	\$

Anti-Tippers

Rear Anti-Tippers	<i>Required safety option.</i>	\$
--------------------------	--------------------------------	----

Backrest

Back Post Style:	Stroller Handle Back				
Back Post Height:	Short (22")	Tall (25")			
	<i>Measured from seat pan to handle.</i>				
Folding Style:	Fold-Down	Non-Folding			
	<i>Fold-down back not compatible with reclining backrest or dynamic rocker back and will be substituted with a non-folding back.</i>				
Seat to Back Angle:	Set at 90°	Set at 98°	Set at 106°	Set at 114°	Set at 122°

Backrest Options

Angle/Height Adjustable Stroller Handle:		\$
Button on Outside	Button on Inside	
Endomorph Back	<i>Backrest will be narrower than seat by total of 2x offset selected. Minimum backrest width is 12". Not compatible with dynamic rocker back or reclining backrest.</i>	\$
1" Offset Per Side	1.5" Offset Per Side	2" Offset Per Side
Spring Back Suspension	<i>Not compatible with reclining back or dynamic rocker back.</i>	\$
Seating Dynamics Dynamic Rocker Back Interface	<i>Not compatible with fold-down back, spring back suspension, endomorph back, or 30° recline. Not available with 20", 21" and 22" seat depths. Finished back post height is 4" taller than selected back post height.</i>	\$

Recline

Reclining Backrest (Manual)	<i>30° maximum recline. Not compatible with backrest extension, spring back suspension, fold-down back, dynamic rocker back or endomorph back. Finished back post height is 3" taller than selected back post height. Limits tilt by up to 20°.</i>	\$
------------------------------------	---	----

Tilt Activation

Attendant Tilt Only

Attendant Tilt Only, Right Back Post	No charge
Attendant Tilt Only, Left Back Post	No charge
Two Trigger Setup	<i>A trigger mounted on each side of the stroller handle. Reduces grip force required to activate tilt. Not compatible with reclining backrest or drum brakes.</i> No charge

User Tilt Only | *Not available on widths greater than 22". Full length arm pads only.*

User Tilt Only, Right Armrest	\$
User Tilt Only, Left Armrest	\$

Attendant & User Tilt | *Not compatible with tall (25") back posts or reclining backrest. Full length arm pads only.*

Attendant & User Tilt Operation	\$
--	----

Attendant Trigger Position:	Right Back Post	Left Back Post
User Trigger Position:	Right Armrest	Left Armrest

Tilt Limit | *Optional. If no tilt limit is selected the full tilt range will be available.*

Tilt Limit:	Set at 15°	Set at 25°	Set at 35°
--------------------	------------	------------	------------

Anterior Pre-Tilt | *Add up to 5° of Anterior Tilt to the tilt range.*

Anterior Pre-Tilt	Set at 0° (Default)	Set at 5°
--------------------------	---------------------	-----------

Power Tilt | 250lbs (113kg) weight capacity. 45° tilt range. Includes 2 batteries for off-chair charging. Power tilt is compatible with either O2 holder or IV pole, not both.

Standard Power Tilt	\$
Power Tilt with Manual Tilt Override Allows for instant manual release of tilt in case of power tilt failure.	\$
Toggle Switch Control	No charge
Installed on Right Installed on Left	
Button Switch Control	No charge
Installed in Right Installed in Left	
Stealth Egg Switch Control Not installed.	No charge
Swing-Away Mounting Hardware Only for Stealth egg switch. Not compatible with all headrest makes and models.	\$

Front Rigging

No Front Rigging	No charge
-------------------------	-----------

Easy-Out Front Rigging | Effortless insertion and removal. No hanger brackets remain on the frame.

Fixed 70°	\$
Universal Adjustable Angle (0°-100°) Select angle. Angle adjustment by loosening one bolt, in 10° increments. Tool-free leg length adjustment. Front rigging may interfere with castors in the 90°-100° settings.	\$
0° 10° 20° 30° 40° 50° 60° 70° 80° 90° 100°	
High Mount Option for Easy-Out Adjustable Angle For shorter lower leg lengths of 8"-12.5".	\$

Swing Away Front Rigging | Legacy design. Not compatible with Easy-Out.

Swing Away 60°	No charge
Swing Away 70°	No charge
Swing Away Elevating Legrests (ELR) Includes calf pads.	\$
1" Offset Hangers for Swing Away Front Rigging	\$

Plug In Front Rigging | Legacy design. Not compatible with Easy-Out.

Plug In 70°	No charge
--------------------	-----------

Footplates

Composite Footplates	No charge
Alumnum Angle Adjustable Footplates	\$
One Piece Fixed Footplate Available on plug in front rigging only. Requires selection of composite or aluminum angle adjustable footplates.	\$
One Piece Flip-Up Footplate Requires selection of composite or aluminum angle adjustable footplates.	\$
Interlocking Angle Adjustable Footplates Available for seat widths up to 21"	\$

Extension Tubes | Consider the height of your seat cushion.

Standard Extension Tubes, Short 8"-12.5" for Easy-Out high mount; 14"-18" for Easy-Out; 13"-17" for swing away and plug in.	No charge
Standard Extension Tubes, Long 11"-16" for Easy-Out high mount; 18"-24" for Easy-Out; 15"-19" for swing away and plug in.	\$

Footplate Height:

Specify:

Ext	Short	8" - 13"	11" - 16"	12" - 16"	13" - 16"
	Long	N/A	14" - 22"	14" - 19"	14" - 17"
		High Mount Easy-Out	Standard Easy-Out	60°, 70°, ELR Swing-Away	Standard Plug-In
Legrest					

Front Rigging Accessories

Calf Pads, Easy-Out Front Rigging	<i>Not compatible with gel padding. Includes reinforced premium calf pad mount.</i>	\$
Calf Pads, Swing Away Front Rigging	<i>Not compatible with gel padding.</i>	\$
Gel Padding	<i>Not compatible with calf pads or Easy-Out front rigging.</i>	\$
Gel Knee Pads, Easy-Out Angle Adjustable Front Rigging		\$
Gel Knee Pads, Swing Away ELR Front Rigging		\$
Length Adjustable Heel Loops		\$
Standard Calf Strap		\$

Positioning Belts

Q'Straint Lap Belt	<i>Model S5-6329-11. For use with WC-19 Transit Tie Down System. 24"-51" belt length.</i>	\$
---------------------------	---	----

Miscellaneous Options

Spoke Guards	<i>Available for 20"-24" composite rear wheels. Made from durable and lightweight aluminium.</i>	\$
Black	Frame color	
Gel Hip Guides	<i>Reduces available seat width by 2"</i>	\$
IV Pole	<i>Not compatible with attendant wheel locks.</i>	\$
Installed on Right	Installed on Left	
O2 Holder	<i>Not compatible with attendant wheel locks.</i>	\$
Installed on Right	Installed on Left	
Medical Necessities Backpack	<i>Black with Permobil logo.</i>	\$
Rubber Shroud for Caster Journals		\$
Adhesive Back Hook Strip	<i>For cushion mounting, 2"x30".</i>	\$

General

Permobil manufactures PDG wheelchairs in a wide variety of configurations to meet the varied needs of wheelchair users. The final selection of a particular model, its options and accessories, and its measurements rests solely with the wheelchair user and the advising healthcare professional. These wheelchairs must be fitted by a qualified healthcare professional. Prices, standard features, options and accessories are subject to change without notice. All rights reserved.

Notes